



Masimo Chemicals South Africa (Pty) Ltd

Technical Data Sheet

Hexane (Polymerisation grade)

Trade Name	Hexane (Polymerisation Grade)
Product Code	MAS 2008
Region	Europe
Product Category	Special Boiling Point Solvents
CAS Registry	64742-49-0
EINECS Number	265-151-9

Description Hexane Polymerisation Grade is manufactured to the high standards required by the polymerisation industry. The solvent contains about 50% n-hexane, with a similar content of other hexane isomers. It is very low in impurities such as aromatics, olefins, carbonyls and acid substances.

Typical Properties

Property	Unit	Method	Value
Density @15°C	kg/l	ASTM D4052	0.675
Cubic Expansion Coefficient @20°C	(10 ⁻⁴)/°C	Calculated	13
Refractive Index @20°C	-	ASTM D1218	1.379
Color	Saybolt	ASTM D156	30
Bromine Index	mg Br/100g ASTM D1492	< 5	
Doctor Test	-	ASTM D235	Negative
Non Volatile Matter	mg/100ml	ASTM D1353	< 0.5
Distillation, IBP	°C	ASTM D1078	66
Distillation, DP	°C	ASTM D1078	70
Relative Evaporation Rate (nBuAc=1)	-	ASTM D3539	8
Relative Evaporation Rate (Ether=1)	-	DIN 53170	1.4
Antoine Constant A #	kPa, °C	-	7.3807
Antoine Constant B #	kPa, °C	-	2110.27
Antoine Constant C #	kPa, °C	-	326.2
Antoine Constants: Temperature range °C	-	+20 to	+70
Vapor Pressure @0°C	kPa	Calculated	8.2
Vapor Pressure @20°C	kPa	Calculated	19
Saturated Vapor Concentration @20°C g/m ³	Calculated	681	
Paraffins	% m/m	GC	85
Naphthenes	% m/m	GC	15
Aromatics	mg/kg	SMS 2728	< 5
Benzene	mg/kg	GC	< 3
n-Hexane	% m/m	GC	52
Sulfur	mg/kg	SMS 1897	< 0.5
Flash Point	°C	IP 170	-30
Auto Ignition Temperature	°C	ASTM E659	375
Explosion Limit: Lower	%v/v	-	1.1
Explosion Limit: Upper	%v/v	-	7.4

Property	Unit	Method	Value
Electrical Conductivity @20°C	pS/m	-	< 1
Dielectric Constant @20°C	-	-	1.9
Aniline Point	°C	ASTM D611	65
Kauri-Butanol Value	-	ASTM D1133	31
Pour Point	°C	ASTM D97	< -50
Surface Tension @20°C	mN/m	Du Nouy ring	19
Viscosity @25°C	mm ² /s	ASTM D445	0.49
Hildebrand Solubility Parameter	(cal/cm ³) ^½	-	7.3
Hydrogen Bonding Index	-	-	0
Fractional Polarity	-	-	0
Heat of Vaporization @Tboil	kJ/kg	-	333
Heat of Combustion (Net) @25°C	kJ/kg	-	46000
Specific Heat @20°C	kJ/kg/°C	-	2.2
Thermal Conductivity @20°C	W/m/°C	-	0.12
Molecular Weight	g/mol	Calculated	86
(#) In the Antoine temperature range, the vapor pressure P (kPa) at temperature T (°C) can be calculated by means of the Antoine equation: $\log P = A - \frac{B}{T+C}$			

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

[American Society for Testing and Materials \(ASTM\) : www.astm.org](http://www.astm.org)

Energy Institute (IP) : www.energyinst.org.uk

Deutsches Institut für Normung (DIN) : www.din.de

For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained through your local Masimo Chemicals South Africa (Pty) Ltd.

Quality

Hexane Polymerisation Grade can be supplied to meet the requirements of ASTM D1836. Hexane Polymerisation Grade does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds

Storage and Handling

Provided proper storage and handling precautions are taken we would expect Hexane Polymerisation Grade to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Material Safety Data Sheet on www.masimochem.com

Hazard Information

For detailed Hazard Information please refer to the Material Safety Data Sheet on www.masimochem.co.za

Trademark

MasimoSol is a Masimo Chemicals South Africa (Pty) Ltd trademark identity.

Warranty / Disclaimer

All products purchased or supplied by Masimo Chemicals companies are subject to the terms and conditions set out in the contract, order confirmation and/or bill of lading. All other information supplied by Masimo Chemicals companies, including that herein, is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine a product's suitability for a particular purpose. Except as may be set forth in the applicable contract, order confirmation and/or bill of lading, Masimo Chemicals companies make no warranty, express or implied, including regarding any information supplied or the data upon which it is based on the results to be obtained from the use of such products or information, or concerning product, whether of satisfactory quality, merchantability, fitness for any particular purpose or otherwise, or with respect to intellectual property infringement as a result of use of information or products, and none shall be implied.

