

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

Product name	MasimoSol 2325
Product Code	MAS 2001
CAS –No.	64742-81-0
Supplier	Masimo Chemicals South Africa (PTY) Ltd G9 Arbour Grove Office Park 10 Oppenheimer Road Amanzimtoti, Durban,4120
Emergency Telephone - South Africa	+27 (0)82 430 9754 +27 (0)83 638 0165

**Recommended use of the chemical and restrictions on use**

Recommended use	Industrial Solvent
Restrictions on use	This product must not be used in applications other than the above without first seeking the advice of the supplier

**2. HAZARDS IDENTIFICATION**

**Classification (REGULATION (EC) No 1272/2008)**

Aspiration hazard	Category 1
Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)
Chronic aquatic toxicity	Category 2

**Label elements**

Hazard pictograms :



Signal word : Danger

• Health Statement

**PHYSICAL HAZARDS:**

Not classified as a physical hazard according to CLP criteria

**HEALTH HAZARDS:**

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Peripheral nervous system) through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H412 Harmful to aquatic life with long lasting effects

- Supplemental Hazard  
EUH066 Repeated exposure may cause skin dryness or cracking.
- Precautionary Statements  
**Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.  
P331 Do NOT induce vomiting.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell.
- Other Hazards  
In use, may form flammable/explosive vapour-air mixture. This material is a static accumulator. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Slightly irritating to respiratory system. Possibility of organ or organ system damage from prolonged exposure; see Chapter 11 for details. Target organ(s): Auditory system

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration No	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Kerosene (petroleum), hydrodesulfurized	64742-81-0	Xn; R65-R66- R67 R52/53	Asp. Tox. 1; H304 STOT SE; H336 Aquatic Chronic 3; H412 EUH066	100

For explanation of abbreviations, see section 16.

#### Further information

Contains:

Chemical Name	Identification Number	Concentration [%]
Naphthalene	91-02-3, 202-049-5	-<=0,1

#### 4. FIRST-AID MEASURES

- General Advice  
DO NOT DELAY.  
Keep victim calm. Obtain medical treatment immediately.
- If Inhalation  
Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment
- In case of Skin Contact  
Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- In case of Eye Contact  
Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention
- If Swallowed  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3° C), shortness of breath, chest congestion or continued coughing or wheezing.
- Most Important Symptoms and Effects, Both Acute and Delay  
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.  
  
Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
  
The onset of respiratory symptoms may be delayed for several hours after exposure.
- Protection for First-Aiders  
When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Notes to Physician  
Potential for chemical pneumonitis.  
Call a doctor or poison control centre for guidance.

## 5. FIRE-FIGHTING MEASURES

- Suitable Extinguishing Media  
Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable Extinguishing Media  
Do not use water in a jet.
- Specific hazards during fire fighting  
Clear fire area of all non-emergency personnel.  
Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide. Unidentified organic and inorganic compounds.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.
- Specific extinguishing methods  
Standard procedure for chemical fires.  
Keep adjacent containers cool by spraying with water.
- Special protective equipment for firefighters  
Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

## 6. ACCIDENTAL RELEASE MEASURE

Observe all relevant local and international regulations.

- Personal Precautions, Protective Equipment and Emergency Procedures  
Observe all relevant local and international regulations.  
Notify authorities if any exposure to the public or the environment occurs or is likely to occur.  
Local authorities should be advised if significant spillages cannot be contained.  
  
Avoid contact with skin, eyes and clothing.  
Isolate hazard area and deny entry to unnecessary or unprotected personnel.  
Do not breathe fumes, vapour.  
Do not operate electrical equipment
- Environmental Precautions  
Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to

avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Monitor area with combustible gas indicator.

- **Methods And Materials For Containment and Cleaning Up**  
For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Ventilate contaminated area thoroughly. If contamination of site occurs, remediation may require specialist advice.
- **Additional Advice**  
For guidance on selection of personal protective equipment, see Chapter 8 of this Safety Data Sheet.  
For guidance on disposal of spilled material, see Chapter 13 of this Safety Data Sheet.

## 7. HANDLING AND STORAGE

- **General Precautions**  
Avoid breathing of or direct contact with material. Only use in well-ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment, see Chapter 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Ensure that all local regulations regarding handling and storage facilities are followed.
- **Advice On Safe Handling**  
Avoid inhaling vapour and/or mists.  
Avoid contact with skin, eyes and clothing.  
Extinguish any naked flames. Do not smoke. Remove ignition sources.  
Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink

The vapour is heavier than air, spreads along the ground and distant ignition is possible.

- Avoidance Of Contact
  - Strong oxidising agents
- Product Transfer
  - Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation.
  - Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
  - Refer to guidance under handling section
- **Storage**
  - Conditions For Safe Storage
    - Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
  - Other Data
    - Storage Temperature: Ambient.
    - Bulk storage tanks should be diked (bunded).
    - Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.
    - Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products, which are not harmful or toxic to man or, to the environment.
    - Electrostatic charges will be generated during pumping.
    - Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.
    - The vapours in the headspace of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
- Packing Material
  - Suitable material: For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint
  - Unsuitable material: Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container Advice
  - Do not cut, drill, grind, weld or perform similar operations on or near containers.

- Specific Use(s)

Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity). IEC/TS 60079-32-1: Electrostatic hazards guidance.

## 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RCP Dearom. Mineral spirits 175 - 220	Not Assigned	TWA	1.200 mg/m <sup>3</sup>	OEL based on European Hydrocarbon Solvents Producers (CEFIC-HSPA) methodology.
	Further information: Recommended Limit			
Naphthalene	91-20-3	TWA OEL-RL	10 ppm 50 mg/m <sup>3</sup>	ZA OEL
	Further information: Recommended Limit			

- Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances, biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier.

Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods. <http://www.cdc.gov/niosh/> Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/> Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances, <http://www.hse.gov.uk/> Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA),

Germany. <http://www.dguv.de/inhalt/index.jsp> L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

- Engineering Measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include:

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended.

Firewater monitors and deluge systems are recommended.

Eyewashes and showers for emergency use.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking.

Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle.

- Personal Protective Equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

- Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level, which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers.

Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

If air-filtering respirators are suitable for conditions of use:

Select a filter suitable for organic gases and vapours [Type A boiling point >65°C (149°F)].



- **Hand Protection**

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. Longer-term protection: Nitrile rubber gloves. Incidental contact/Splash protection: PVC or neoprene rubber gloves. For continuous contact, we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
- **Eye Protection**

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- **Skin and body protection**

Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron.  
Wear antistatic and flame retardant clothing, if a local risk assessment deems it so.
- **Thermal Hazard**

Not applicable
- **Hygiene Measures**

Wash hands before eating, drinking, smoking and using the toilet. Launder contaminated clothing before re-use.  
Do not ingest. If swallowed then seek immediate medical assistance
- **Environmental Exposure Controls**

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation. Information on accidental release measures are to be found in section 6.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Colourless
Odour	Aromatic
Odour Threshold	Data not available
pH	Not applicable
Melting / Freezing Point pour point	Data not available < -30 °C / -22 °F
Boiling point and boiling range	Typical 215 - 250 °C / 419 - 482 °F
Flash Point	Typical 89 °C / 192 °F
Evaporation rate	0,01 Method: ASTM D 3539, nBuAc=1
Flammability (solid, gas)	Not applicable
Upper Explosion Limits	6,5 %(V)
Lower Explosion Limits	0,7 %(V)
Vapour Pressure	Typical 0,01 Pa (20 °C / 68 °F)
Relative vapour density	Data not available
Relative density	Data not available
Density	814 g/cm <sup>3</sup> (20 °C / 68 °F) Method: ASTM D4052
Water Solubility	Data not available
Partition coefficient: n-octanol/water	Data not available
Auto-ignition temperature	Data not available
Decomposition temperature	Data not available
Viscosity	
Viscosity, dynamic	Data not available
Viscosity, Kinematic	2,2 mm <sup>2</sup> /s Method: ASTM D445
Explosive properties	Not applicable
Oxidising properties	Data not available
Surface tension	Data not available
Conductivity	Low conductivity: < 100 pS/m The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi- conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
Molecular weight	174 g/mol

## 10. STABILITY AND REACTIVITY

- **Reactivity**  
The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
- **Chemical Stability**  
No hazardous reaction is expected when handled and stored according to provisions. Stable under normal conditions of use.
- **Possibility of Hazardous Reactions**  
Reacts with strong oxidising agents
- **Conditions to Avoid**  
Avoid heat, sparks, open flames and other ignition sources.  
In certain circumstances product can ignite due to static electricity.
- **Incompatible Materials**  
Strong oxidising agents
- **Hazardous Decomposition Products**  
Hazardous decomposition products are not expected to form during normal storage.  
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

## 11. TOXICOLOGICAL INFORMATION

- **Basis for Assessment**  
Information given is based on product testing, and/or similar products, and/or components.
- **Information on likely Route of Exposure**  
Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact and accidental ingestion.
- **Acute Oral Toxicity**  
Expected to be low toxicity: LD50 Rat: > 5000 mg/kg
- **Acute Inhalation Toxicity**  
Remarks: Expected to be of low toxicity:  
LC50 greater than near-saturated vapour concentration.  
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea
- **Acute Dermal Toxicity**

Expected to be low toxicity: LD50 Rat: > 5000 mg/kg

- **Skin Corrosion/Irritation**  
Causes skin irritation. Prolonged repeated contact may cause defatting of the skin, which can lead to dermatitis.
- **Serious Eye Damage / Eye Damage**  
Expected to be non-irritating to eyes.
- **Respiratory or Skin Sensitisation**  
Not expected to be a sensitiser.
- **Germ Cell Mutagenicity**  
Not mutagenic
- **Carcinogenicity**  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Material	GHS/CLP Carcinogenicity Classification
Kerosene (petroleum), hydrodesulfurized	No carcinogenicity classification.
Naphthalene	Carcinogenicity Category 2
Naphthalene	IARC: Group 2B: Possibly carcinogenic to humans

- **Reproductive Toxicity**  
Causes foetotoxicity in animals at doses, which are maternally toxic. Not expected to impair fertility
- **STOT – Single Exposure**  
Inhalation of vapours or mists may cause irritation to the respiratory system.
- **STOT – Repeated Exposure**  
Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment cause hearing loss. Central nervous system: repeated exposure affects the nervous system. Kidney: caused kidney effects in male rats, which are not considered relevant to humans.
- **Aspiration Toxicity**  
Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis, which can be fatal.
- **Further Information**  
Classifications by other authorities under varying regulatory frameworks may exist.

## 12. ECOLOGICAL INFORMATION

- Basis for assessment

Incomplete ecotoxicological data are available for this product. The information given below is based partly on knowledge of the components and the ecotoxicology of similar products.

### Acute Toxicity

- |                          |   |
|--------------------------|---|
| • Fish                   | Harmful LL/EL/IL50 > 10-100 mg/l            |
| • Crustacean             | Practically non toxic: LL/EL/IL50 > 100mg/  |
| • Algae / Aquatic Plants | Harmful LL/EL/IL50 > 10-100 mg/l            |
| • Microorganisms         | Expected to be harmful: LL/EL/IL50 > 100mg/ |

### Chronic Toxicity

- |                                 |   |
|---------------------------------|---|
| • Fish                          | Data not available  |
| • Crustacean                    | Data not available  |
| • Persistence and degradability | Biodegradability<br>Expected to be readily biodegradable. Oxidises rapidly by photochemical reactions in air. |
| • Bioaccumulation               | Has the potential to bioaccumulation<br>Partition coefficient: n-octanol/water:<br>Data not available         |
| • Mobility in Soil              | Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile                   |
| • Other adverse effects         | No Data available   |

## 13. DISPOSAL CONSIDERATIONS

- Waste from residues

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in watercourses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Local regulations may be more stringent than regional or national requirements and must be complied with.

- Contaminated packing

Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

Send to drum recover or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.

#### 14. TRANSPORT INFORMATION

**IATA –DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of Marpol 73/78 and IBC Code**

Pollution category : Annex I  
Ship type : Annex I or Double hull vessels with carriage of oil certificate  
Product name : Kerosene

- Special Precautions for User  
Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions, which a user needs to be aware of or needs to comply with in connection with transport.
- Additional Information  
This product may be transported under nitrogen blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen-enriched atmospheres displaces available oxygen, which may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

#### 15. REGULATORY INFORMATION

- a. Safety, health and environmental regulations/legislation specific for the substance or mixture. The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.
- b. The components of this product are reported in the following inventories:

AICS	: Listed
DSL	: Listed
IECSC	: Listed
ENCS	
KECI	: Listed
NZIoC	: Listed
PICCS	
TCSI	: Listed
TSCA	: Listed

## 16. OTHER INFORMATION

Full text of R-Phrases	
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements	
EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Full text of other abbreviations	
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
STOT SE	Specific target organ toxicity - single exposure

### a. Abbreviations and Acronyms

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

### SDS Regulations

#### b. Training Advice

Provide adequate information, instruction and training for operators.

#### c. Other Information

A vertical bar (|) in the left margin indicates an amendment from the previous version.

**Due to a change of detail in Section 1, this document has been released as a significant change.**

#### d. Source of key data compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.